



# STANDARD MOTORS



# ASYNCHRONOUS MOTOR IP55

## CAST IRON



- ✓ IE2 & IE3, IE4, IE5 to follow
- ✓ 230/400V – 400/690V – 500V
- ✓ Frame size 71 to 560mm
- ✓ 0,25kW - 1,4MW
- ✓ 2,4,6 & 8 poles in stock
- ✓ 10 & 12 P on request
- ✓ T° rise B – Insulation F
- ✓ Winding PTC 150°C included
- ✓ NU bearings @DE from size 315mm
- ✓ B3, B5, B35, V1 - IC411

# ASYNCHRONOUS MOTOR IP55

## ALUMINIUM



- ✓ IE2 & IE3, IE4, IE5 to follow
- ✓ 230/400V – 400/690V – 500V
- ✓ Frame size 71 to 160mm
- ✓ 0,25kW – 18,5kW
- ✓ 2,4 & 6 poles in stock
- ✓ 8, 10 & 12 P on request
- ✓ T° rise B – Insulation F
- ✓ Winding PTC 150°C included
- ✓ Ball bearings @DE & @NDE
- ✓ B3, B5, B35, V1 - IC411

# ASYNCHRONOUS MOTOR IP23

## CAST IRON



- ✓ IE2 & IE3, IE4, IE5 to follow
- ✓ 230/400V – 400/690V – 500V
- ✓ Frame size 71 to 400mm
- ✓ 18,5kW – 710kW
- ✓ 2,4 & 6 poles in stock
- ✓ 8, 10 & 12 P on request
- ✓ T° rise B – Insulation F
- ✓ Winding PTC 150°C included
- ✓ Ball bearings @DE & @NDE
- ✓ B3, B5, B35, V1 - IC411

# SECOND HAND ELECTRICAL MATERIAL

- ✓ Squirrel cage asynchronous Motor IP55 & IP23 Low Voltage  
→ up to 1MW
- ✓ Squirrel cage asynchronous Motor Medium voltage  
→ up to 4MW
- ✓ DC Motors  
→ up to 1MW
- ✓ Transfomators Medium Voltage ( 6-11-15 and 20kV)  
→ up to 3MVA )

